Ordinance 22-040

An Ordinance to amend Chapter 94, Zoning of the City of Brookings pertaining to Sections 94-131, 94-132, 94-133, 94-134, 94-135, 94-135.5, 94-136, 94-137, 94-161, and 94-399.1 for the purposes of Amending the Maximum Allowable Heights in the B-1, B-2, B-2A, B-3, B-4, B-5, I-1, I-1R and I-2 Districts and Associated Bufferyard Requirements.

Be It Ordained by the Governing Body of the City of Brookings, South Dakota that the Subdivision Regulations be amended as follows:

I.

ARTICLE IV. - DISTRICT REGULATIONS

That the following sections of Article IV of the Zoning Regulations shall be amended to read as follows:

Sec. 94-131. Business B-1 central district.

(f) Density, area, yard and height regulations. The B-1 district regulations are as follows:

		Density Sq. Ft.	Min. Lot Area	Min. Lot Width	Min. Front	Min. Side	Min. Rear	Max. Height
			Sq. Ft.		Yard	Yard	Yard	
-	All uses					*	20 feet*	60 feet

^{*}Refer to section 94-399.1 bufferyards.

Sec. 94-132. Business B-2 district.

(f) Density, area, yard and height regulations. The density, area, yard and height regulations in the B-2 district are as follows:

	Density Sa. Ft.	Min. Lot Area	Min. Lot Width	Min. Front	Min. Side	Min. Rear	Max. Height
	34. Ft.	Sq. Ft.	viatii	Yard	Yard	Yard	Leignt
Commercial uses		15,000	100 feet	25 feet	5 feet*	20 feet*	60 feet
Other allowable		15,000	100 feet	25 feet	7 feet**	20 feet	60 feet
uses							

^{*}Refer to section 94-399.1 bufferyards.

Sec. 94-133. Business B-2A office district.

(f) Density, area, yard and height regulations. The B-2A district regulations are as follows:

	Density	Min. Lot	Min. Lot	Min.	Min.	Min.	Max.
	Sq. Ft.	Area	Width	Front	Side	Rear	Height
		Sq. Ft.		Yard	Yard	Yard	
All uses				25 feet	5 feet*	20 feet*	60 feet

^{**}The side yard will be required to be increased to ten feet if the building is three or more stories in height.

*Refer to section 94-399.1 bufferyards.

Sec. 94-134. Business B-3 heavy district.

(f) Density, area, yard and height regulations. The B-3 district regulations are as follows:

	Density	Min. Lot	Min. Lot	Min.	Min.	Min.	Max.
	Sq. Ft.	Area	Width	Front	Side	Rear	Height
		Sq. Ft.		Yard	Yard	Yard	
All uses				20 feet	5 feet*	20 feet*	60 feet

^{*}Refer to section 94-399.1 bufferyards.

Sec. 94-135. Business B-4 highway district.

(f) Density, area, yard and height regulations. The B-4 district regulations are as follows:

	Density Sq. Ft.	Min. Lot Area Sa. Ft.	Min. Lot Width	Min. Front Yard	Min. Side Yard	Min. Rear Yard	Max. Height
All uses		40,000*	200 feet**	50 feet	25 feet***	30 feet***	N/A***

^{*}A lot fronting on a service road or non-arterial right-of-way must have a minimum lot area of 30,000 square feet.

Sec. 94-135.5. Business B-5 planned research and business district.

(f) Density, area, yard and height regulations. The density, area, yard and height regulations in the B-5 district are as follows:

	Density	Min. Lot	Min. Lot	Min.	Min. Side	Min. Rear	Max.
	Sq. Ft.	Area	Width	Front	Yard	Yard	Height
		Sq. Ft.		Yard*			
All uses				40 feet	25 feet**	30 feet**	N/A**

^{*}The yard abutting Interstate 29 shall be considered a front yard.

Sec. 94-136. Industrial I-1 light district.

(f) Density, area, yard and height regulations. The I-1 district regulations are as follows:

	Density	Min. Lot	Min. Lot	Min. Front	Min. Side	Min. Rear	Max.
	Sq. Ft.	Area	Width	Yard	Yard	Yard	Height
		Sq. Ft.					
All uses				20 feet	20 feet*	20 feet*	N/A*

^{*}Refer to section 94-399.1 bufferyards.

Sec. 94-137. Industrial I-2 heavy district.

(f) Density, area, yard and height regulations. The I-2 district regulations are as follows:

^{**}A lot fronting on a service road or non-arterial right-of-way must have a minimum lot width of 150 feet.

^{***}Refer to section 94-399.1 bufferyards.

^{**}Refer to section 94-399.1 bufferyards.

	Density Sq. Ft.	Min. Lot Area Sa. Ft.	Min. Lot Width	Min. Front Yard	Min. Side Yard	Min. Rear Yard	Max. Height
All uses				40 feet	20 feet*	20 feet*	N/A*

^{*}Refer to section 94-399.1 bufferyards.

Sec. 94-161. Industrial I-1R restricted district.

(f) Density, area, yard and height regulations. The I-1R district regulations are as follows:

	Lot Coverage	Min. Lot Area Sq. Ft.	Min. Lot Width	Min. Front Yard	Min. Side Yard	Min. Rear Yard	Max. Height
All uses	35%*			60 feet***	50 feet**	50 feet**	N/A**

^{*}Buildings used solely for storage and/or warehousing operations may occupy no more than 50 percent of the area of the lot.

11.

ARTICLE VI. - SUPPLEMENTAL REGULATIONS

That the following sections of Article VI of the Zoning Regulations shall be amended to read as follows:

Sec. 94-399.1. Bufferyards.

- (d) Bufferyard requirements.
 - (1) Bufferyards are required in accordance with the following table.

Table 1.1

	Zoning of Abutting	Proposed Buildings	Proposed Buildings	Solid Fence/Wall or
	Land	over 30' in Height	over 60' in Height	Continuous Shrubs
Zoning of Proposed	R-1, R-1A, R-1B, R-	R-1, R-1A, R-1B, R-		R-1, R-1A, R-1B, R-1C,
Development	1C, R-1D, R-2, R-3,	1C, R-1D, R-2, R-3,		R-1D, R-2, R-3, R-3A,
	R-3A, RMH	R-3A, RMH		RMH
B-1	Type A or type F	Type B or type F	N/A	N/A
B-2	Type B or type G	Type C or type G	N/A	N/A
B-2A	Type A or type E	Type C or type G	N/A	N/A
R-B4	Type A or type E	Type C or type G	N/A	N/A
B-3	Type C or type H	Type C or type H	N/A	6' required
B-4	Type C or type G	Type C or type G	Type D or type I	6' required
B-5	Type C or type G	Type C or type G	Type D or type I	N/A
I-1, I-1R	Type C or type H	Type C or type H	Type D or type J	6' required
I-2	Type C or type H	Type C or type H	Type D or type J	6' required
*R-3, R-3A, R-B4		Type B or type G	N/A	N/A

^{*}Applicable only to structures over 30 feet in height.

^{**}Refer to section 94-399.1 bufferyards.

^{***}The yard area abutting Interstate 29 shall be considered a rear yard.

(2) Bufferyard types. The following bufferyard types are hereby established and shall provide the requirements for each type of bufferyard referenced in table 1.1. The table prescribes the minimum widths and landscaping for bufferyards.

Table 1.2

Bufferyard	Minimum	Minimum	Plantings per 100 lineal feet or fraction thereof per Bufferyard				
Types	Buffer from Buffer to						
	Parking Lot	Structure					
Type A	10'	20'	3 trees and 10 shrubs				
Туре В	15'	25'	5 trees and 10 shrubs				
Type C	20'	30'	6 trees and 14 shrubs				
Type D	30′	45'	6 trees and 14 shrubs				
Type E	25'	25'	greenspace				
Type F	30'	30'	greenspace				
Type G	40'	40'	greenspace				
Туре Н	50'	50'	greenspace				
Type I	60′	60'	greenspace				
Type J	75'	75′	greenspace				

III.

All ordinances and parts of ordinances in conflict herewith are hereby repealed.

First Reading:

November 22, 2022

Second Reading:

December 13, 2022

Published:

December 16, 2022

CITY OF BROOKING

Oepke "pe" Niemeyer, Mayer

ATTEST:

mie Foster, City Clerk